



P.O. BOX 2084 • 207 RECYCLING WAY
DALTON, GA 30720
706.217.1900 • FAX:706.217.1904
TOLL FREE: 855.803.5092

36 OZ ULTRA DS SPECIFICATIONS

WEIGHT	36 OZ. DS
THICKNESS	0.375
DENSITY lbs./cu. ft.	9.0
TENSILE STRENGTH:	
LENGTH	215
WIDTH	229
PILL TEST	PASS
FHA TYPE/CLASS	H 1 & 2
RADIANT PANEL-ASTME 648	CLASS 1
STT	74
TVOC	1.00 MG
BHT	0.30 MG
FORMALDEHYDE	0.05 MG
4-PC	0.05 MG
ROLL WIDTH	6'/12'
ROLL LENGTH	60'/60'
ROLL WEIGHT	80 LBS

Manufactured with an attached extruded poly propylene foam product. Contains microban antimicrobial protection.

WARRANTY:

American Fiber Company, Inc. warrants that its manufactured products are free from any defects in workmanship and material, will provide satisfactory service and a lively and resilient foundation for the life of the carpet under which it is originally installed. This warranty applies only when properly installed over flat, smooth, hard surfaces on or above grade. The synthetic fiber is mold, moth, mildew, and odor resistant and can be used below grade.

American Fiber Company, Inc. as a sole and exclusive remedy, will replace, without charge, any manufactured product which does not render satisfactory service in normal use F.O.B. manufacturing plant. This warranty does not include the cost of removal or installation. No liability will be assumed for any consequential damage, loss, or expense.